



PO BOX 9699
Bloemfontein
9300

Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

FLEETLINE ENGINE OIL SJ /CF 4 SAE 20W50

APPLICATION

It is a range of engine oils blended from virgin base oils, which have been fortified with performance additive. Recommended for naturally-aspirated and mildly turbo charged diesel and petrol engines.

PERFORMANCE LEVEL (API SJ/CF 4

MEETS OR EXCEEDS:

- **MB 227.0 MB 227.1**
- **US MIL-L-46152E AND MIL-L-2104B**
- **ADE Pg 3**
- **ACEA E3-96 ISUZU, ES-99,B3-98,A3-98**
- **MAN 3275**
- **MAC T9, MAC T8A, CAT1-A**
- **MAC EOM PLUS**
- **API SJ/CF 4**
- **VOLVO VDS-2**
- **CUMMINS 20072, 20076, 20077**

- Specially designed combination of detergent and dispersant additives maintains power output by controlling piston and ring deposits.
- Heavy duty engine protection in new and older engines
- High temperature deposit control in turbo charged and naturally aspirated engines
- Robust against a wide range of diesel quality
- Premium 500+ and sludge handling and oxidation stability
- Strong diesel detergency for high level piston cleanliness and extended drain capability.
- Superior wear and bearing corrosion control giving maximum engine protection.

TYPICAL PHYSICAL CHARACTERISTICS	SAE 20 w 50
Density @ 20°c KG / L	0.894
Viscosity Cst @ 40° c	147
Viscosity Cst @ 100° c	17.8
Viscosity Index	132
Pour Point °c (Max)	-18
Flash Point °c (Min)	250
TBN mg KOH/G	11