



PO BOX 9699
Bloemfontein
9300

Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

ATF DXIII

ATF is an automatic transmission fluid for use where manufacturers call for a Dexron III fluid. It is blended from virgin base oils, which have been fortified with anti-wear anti-oxidant, anti-foam, anti-corrosion and viscosity index improvers together with friction modifiers. This blend of components gives high levels of performance and long service life.

APPLICATION

- Automotive heavy-duty automatic transmissions
 - Power shift transmissions
 - Power steering
 - Certain manual transmissions
- Hydraulic systems
Screw type air compressor

PERFORMANCE LEVEL

MEETS OR EXCEEDS:

- DEXRON III
 - DAIMLER BENZ 236.1
 - DENISON HF-0
 - ZF TE – ML 09/11/14
 - VOITH
- ALLISON C-3
 - CAT TO-2

BENEFITS

Excellent anti wear properties ensure longer equipment life.

TYPICAL PHYSICAL CHARACTERISTICS	ATF
Density @ 20 °C KG/L	0,857
Viscosity Cst @ 40 °C	33
Viscosity Cst @ 100 °C	7,2
Viscosity index	189
Pour point °C(MAX)	-47
Flash point °C (MIN)	210