



PO BOX 9699  
Bloemfontein  
9300  
Fax: 051 433 4337  
Mobile: 082 800 4599  
E-mail: [bertus@fleetline.co.za](mailto:bertus@fleetline.co.za)  
Website: [www.fleetline.co.za](http://www.fleetline.co.za)

### **CLASSIC CUTTERBAR 150**

This cutterbar is specially formulated mineral oil recommended for the lubrication of cutting chains, cutter bars and drive gear on hand-held chain saws. The oil contains a superlative additive pack to ensure that adequate lubricant adheres to the rubbing surfaces of this total loss system. Its exceptionally high viscosity index which means that the product retains its viscometrics even at high operating temperatures, reducing fling-off and protecting the components.

Fleetline Classic 150 is recommended for all makes of hand-held chain saws.

#### **BENEFITS**

- Excellent lubrication and super adhesive-cohesive properties
- Lower oil consumption and extended chain life
- Prevents wear and is cost effective

---

<b>Physical Characteristics</b>	<b>Typical</b>	<b>Test Method</b>
Colour	Amber/Green	Visual
Density @ 40° C	0.86	IP 190
Viscosity cSt @ 40° C	170-220	ASTM D445
Viscosity Index	238	ASTM D2270
Flash Point °C	220	ASTM D92
Total Acid Number	0.6 – 1.1	ASTM D974

---

#### **HEALTH HAZARD DATA:**

Eye contact : Flush with water

Skin contact : Wash contact areas with soap and water

Inhalation : Not expected to be a problem

Ingestion : Not expected to be a problem when ingested. If uncomfortable seek medical assistance.

Extinguishing media : Carbon dioxide, foam, dry chemical and water fog.

Procedure if material is released or spilled: Apply sawdust to spilled material, shovel up and dispose of at an appropriate waste disposal facility in accordance with current applicable laws and regulations, and product characteristics at time of disposal.