



PO BOX 9699
Bloemfontein
9300
Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

GEAR OILS EP90 & EP80W90 (GL-4)

High performance, multipurpose mild extreme pressure gear lubricant

Application

Manual **transmissions**, transaxles, planetary hub & other spur gear axles which specifically require mild EP gear oils meeting API GL-4

Performance level (API GL4)

Meets or exceeds:

- Multipurpose EP or hypoid gear oil
- MIL-2105
- MB 235.1 MB235.5
- MAN 34ML

Benefits

High performance, EP additive system controls transmission gear tooth wear, excellent load carrying capacity to protect gear equipment against surface stress under heavily loaded conditions

GL-4 gear oils have been fortified with anti-wear, anti-oxidant, anti-foam, anti-corrosion and extreme pressure additives

TYPICAL PHYSICAL CHARACTERISTICS	80w90	90
Density @ 20 °C KG/L	0.893	0.9
Viscosity Cst @ 40 °C	150	170
Viscosity Cst @ 100 °C	18	18
Viscosity index	95	95
Pour point °C (MAX)	-22	-15
Flash point °C (MIN)	220	222
Sulphur, WT%	0.4	0.4