



*Oilflow cc*

P O BOX 14527  
WADEVILLE  
1422  
TEL 011 827 5848  
FAX 011 827 5832

BIG ENOUGH TO SERVE – SMALL ENOUGH TO CARE

## **EP 140 GL5**

### **DESCRIPTION**

Fleetline EP 140 GL-5 is a high performance, multipurpose EP gear lubricant for differentials, manual transmissions and other gear cases of automotive equipment.

### **PERFORMANCE STANDARD**

Fleetline EP 140 GL 5 meets the requirements of:

- API Service categories GL5
- MIL-L-2106D and MIL-L-2105B (85w)- Former US Military spec
- Mack GO-H and GO-G
- Man 342 N

### **APPLICATION**

Fleetline EP 140 GL 5 is recommended for gear applications requiring lubricants which meet MIL-L-2105D, MIL-L-2105B, API Service GL-5, where EP, multipurpose or hypoid type gear oils are specified. It is particularly suitable where loading is severe and maximum gear protection is required. This product may also be used for top up of limited slip differentials after break in of new or rebuilt units.

### **TYPICAL CHARACTERISTICS**

The physical and chemical properties shown in the table are average values based on recent production. They are not limiting values. Minor variations, which do not affect performance, are to be expected in normal manufacture.

### **KEY PROPERTIES**

GRADE	EP 140
Density @ 20 C,kg/1	0,9
Flash Point (COC), C	228
Kinematic Viscosity	
cST @ 40 C	420
cST @ 100 C	28
Viscosity Index	97
Pour Point C	-18