



PO BOX 9699
Bloemfontein
9300
Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

GL 5 EP85W140 GEAR OIL

DESCRIPTION

Fleetline GL5 EP85w140 is a high performance, multipurpose EP gear lubricant for differentials, manual transmissions and other gear cases of automotive equipment.

PERFORMANCE STANDARD

Fleetline GL5 EP 85w140 meets the requirements of:

- API Service categories GL5
- MIL-L-2105D and MIL-L-2105B (85w)- Former US Military spec
- Mack GO-H and GO-G
- Man 342 N

APPLICATION

Fleetline GL5 EP 85W140 is recommended for gear applications requiring lubricants which meet MIL-L-2105D, MIL-L-2105B, API Service GL-5, where EP, multipurpose of hypoid type gear oils are specified. It is particularly suitable where loading is severe and maximum gear protection is required. This product may also be used for top up of limited slip differentials after break in of new or rebuilt units.

TYPICAL CHARACTERISTICS

The physical and chemical properties shown in the table are average values based on recent production. They are not limiting values. Minor variations, which do not affect performance, are to be expected in normal manufacture.

KEY PROPERTIES

GRADE	85W140
Density @ 20 C,kg/1	0,91
Flash Point (COC), C	238
Kinematic Viscosity	
cST @ 40 C	460
cST @ 100 C	31
Viscosity Index	98
Pour Point C	-18