



PO BOX 9699  
Bloemfontein  
9300  
Fax: 051 433 4337  
Mobile: 082 800 4599  
E-mail: [bertus@fleetline.co.za](mailto:bertus@fleetline.co.za)  
Website: [www.fleetline.co.za](http://www.fleetline.co.za)

## **FLEETLINE GEAR OILS EP 90, EP80W90 (GL –5)**

High performance, multipurpose extreme pressure gear lubricant.

### **Application**

Manual transmissions, transaxles, planetary hub & other spur gear axles which specifically require EP gear oils meeting API GL-5

### **Performance level (API GL5)**

Meets or exceeds:

- Multipurpose EP or hypoid gear oil
- MIL-2105 -D
- MB 235.1 MB235.5
- MAN 342N

### **Benefits**

High performance, EP additive system controls transmission gear tooth wear, excellent load carrying capacity to protect gear equipment against surface stress under heavily loaded conditions  
GL-5 gear oils have been fortified with anti-wear, anti-oxidant, anti-foam, anti-corrosion and extreme pressure additives

### ***TYPICAL PHYSICAL CHARACTERISTICS EP80w90 EP 90***

Density @ 20 °C KG/L	0,9	0,9
Viscosity Cst @ 40 °C	171	170
Viscosity Cst @ 100 °C	18	18
Viscosity index	98	98
Pour point °C (MAX)	-22	-17
Flash point °C (MIN)	220	220