



PO BOX 9699
Bloemfontein
9300

Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

HYDRAULIC UHVI 46 and 68 **ZINC TYPE ANTI-WEAR HYDRAULIC FLUID**

DESCRIPTION

Hydraulic UHVI 46 and 68 is premium quality anti-wear hydraulic oil. It is blended from virgin paraffin base oils. It contains anti-wear, anti-rust, anti-oxidant and anti-foam additives to give excellent performance and wear protection. In addition it contains a viscosity index improver to lessen the impact of high operating temperatures. It is recommended for use in any circulating hydraulic system where zinc containing anti-wear hydraulic oil is called for especially those running at higher than normal temperatures.

PERFORMANCE BENEFITS

Hydraulic UHVI 68 and 46 has the following features:

- Rex roth
- Good corrosion protection
- Effective anti-wear properties
- Long equipment life
- Excellent oxidation resistance
- Excellent temperature/viscosity performance
- DIN 51524 Part 3
- Denison HF-0
- Vickers M-2950 S (Mobile Systems)
- M -1286 S (Industrial Systems)

DIRECTIONS FOR USE

Hydraulic UHVI 68 and 46 may be used in any circulating hydraulic system, which calls for the use of anti-wear hydraulic oil containing a zinc anti-wear additive. It is called for whenever the temperature of the system runs hotter than normal to ensure that loss of pressure does not occur due to viscosity drop. It should not be used in a system, which contains silver plated components.

TECHNICAL DATA

ISO Grade	46	68
Viscosity @ 40°C	46	68
Viscosity @ 100°C	6,8	10
Viscosity Index	150	130
Flash Point °C	220	220
Pour Point °C	-33	-30