



PO BOX 9699
Bloemfontein
9300

Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

HEAVY DUTY MULTI PURPOSE GREASE

Product Description

OILFLOW EP 2 LMG is a heavy duty grease with a good thermal stability, outstanding water wash out characteristics, excellent adherence to impart sealing protection and incorporates Molybdenum disulfide and graphite particles which form a slippery coating on metal thus reducing wear and friction.

Application

OILFLOW EP 2 LMG is recommended for use in severe applications, specially where water and environmental contaminants are a problem. It resists shock loads due to the content of solid lubricating additives, ensuring the best protection under the most adverse conditions.

It is highly recommended for ball and slide bearings of heavily loaded and intermittently loaded equipment in the chemical, paper, plastic and steel industry. Earth moving equipment and agricultural machinery, axles, shafts, bushes and other mechanical parts.

Advantages

- . Resist temperature, shocks and vibration
- . Excellent metal adhesion
- . Very good water and contaminants resistance
- . Emergency lubrication through Molybdenum disulfide

Physical Properties

Product type.....Grease
Color.....Black/Grey
Service temperature (°C).....-20 to 120
NLGI consistency.....2

Storage : 18 month - store under cover in a non corrosive environment.

Application : Clean all surfaces to be lubricated. Apply grease with a brush or a grease gun . DO NOT MIX WITH OTHER GREASES.