



PO BOX 9699
Bloemfontein
9300

Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

HYDRAULIC UHVI 46 **ZINC TYPE ANTI-WEAR HYDRAULIC FLUID**

DESCRIPTION

Hydraulic UHVI 46 is a premium quality anti-wear hydraulic oil. It is blended from virgin paraffinic base oils. It contains anti-wear, anti-rust, anti-oxidant and anti-foam additives to give excellent performance and wear protection. In addition it contains a viscosity index improver to lessen the impact of high operating temperatures. It is recommended for use in any circulating hydraulic system where a zinc containing anti-wear hydraulic oil is called for especially those running at higher than normal temperatures.

PERFORMANCE BENEFITS

Hydraulic UHVI 46 has the following features:

- Good corrosion protection
- Effective anti-wear properties
- Long equipment life
- Excellent oxidation resistance
- Excellent temperature/viscosity performance

DIRECTIONS FOR USE

Hydraulic UHVI 46 may be used in any circulating hydraulic system, which calls for the use of anti-wear hydraulic oil containing a zinc anti-wear additive. It is called for whenever the temperature of the system runs hotter than normal to ensure that loss of pressure does not occur due to viscosity drop. It should not be used in a system which contains silver plated components.

TECHNICAL DATA

ISO Grade	46
Viscosity @ 40°C	46
Viscosity @ 100°C	9
Viscosity Index	125
Flash Point °C	220
Pour Point °C	-30