



PO BOX 9699
Bloemfontein
9300
Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

OUTBOARD OIL

DESCRIPTION

Pro Viscous outboard is a premium performance, two stroke, marine outboard motor oil formulated with special additives. Pre-diluted with a high flash point solvent to facilitate mixing with petrol at all temperatures. Designed for engines requiring NMMA TC W3 lubricants.

APPLICATIONS

All water cooled, two stroke, marine outboard engines, oil injected engines, and air cooled two stroke engines where API TD or NMMA oils are specified.

PERFORMANCE STANDARD

Formulated to meet NMMA (National Marine Manufacturers Association) TC W3

API TD
NMMA TC-W2

BENEFITS

Specially blended with virgin refined mineral oil and ashless additive to maintain a high power output. Provide piston cleanliness and protection against ring sticking, and power loss by maintaining combustion efficiency. The special ashless additive enhances lubricity as well as coating surfaces with a tough lubricant to protect against wear under peak performance conditions, reduces spark plug fouling, and ensures that ash induces deposits are not formed in the combustion chamber.

KEY PROPERTIES

Viscosity @ 40	38.13 cst
Flash Point C	-25 C
Ash,m %	0.01