



PO BOX 9699
Bloemfontein
9300

Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

FLEETLINE ENGINE OIL SF/CD

SAE 30/40/50/20W50

APPLICATION

It is a range of engine oils blended from virgin base oils, which have been fortified with performance additive. Recommended for naturally-aspirated and mildly turbo charged diesel and petrol engines.

PERFORMANCE LEVEL (API SF/CD)

MEETS OR EXCEEDS:

- MB 227.0 MB 227.1
- US MIL-L-46152E AND MIL-L-2104B
- ADE Pg 3
- CCMC G4-D2
- SABS 1516
 - Specially designed combination of detergent and dispersant additives maintains power output by controlling piston and ring deposits.
 - Heavy duty engine protection in new and older engines
 - High temperature deposit control in turbo charged and naturally aspirated engines
 - Robust against a wide range of diesel quality

TYPICAL PHYSICAL CHARACTERISTICS	SAE 30	SAE 40	SAE 50	SAE 20W50
Density @ 20°C KG/L	0.892	0.895	0.897	0.886
Viscosity Cst @ 40°C	92	134	220	175
Viscosity Cst @ 100°C	11	14.2	19	19.5
Viscosity Index	105	104	99	125
Pour Point, °C (MAX)	-18	-9	-9	-25
Flash Point, °C (MIN)	240	258	260	220
TBN mg KOH / G	9	9	9	9
Sulphated ASH, m%	1.0	1.0	1.0	1.0
Zinc, m%	0.12	0.12	0.12	0.12