



PO BOX 9699
Bloemfontein
9300
Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

FLEETLINE ENGINE OIL 15W50 SJ/CF-4

DESCRIPTION

Fleetline 15W50 is an advanced technology, motor oil providing superior performance in today's passenger car engines. The use of base fluid in the formulation ensures excellent viscosity retention and superior engine protection under all modern driving conditions.

APPLICATION (MIXED FLEET OIL)

For all naturally aspirated and turbocharged diesel and petrol engines

PERFORMANCE LEVEL (API SJ/CF-4)

MEETS OR EXCEEDS:

- MAN 270 271 and 3275
- MB 228.3/MB 229-1
- ACEA A3 – 98 / B3 - 98
- VOLVO VDS
- FORD MOTORCO. M2C-153E
- ADE SHEET 3 & 4
- VW 501.01 / 505.00
- API SJ/CF-4

BENEFITS

- Excellent engine protection.
- Longer drain periods.
- Reduced chlorine content.

TYPICAL PHYSICAL CHARACTERISTICS		SAE 15w50
Density @ 20°C KG/L		0.89
Viscosity Cst @ 40°C		140
Viscosity Cst @ 100°C		19
Viscosity Index		156
Pour Point, °C (MAX)		-27
Flash Point, °C (MIN)		210
Sulphated ASH, m %		10