



PO BOX 9699
Bloemfontein
9300
Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

FLEETLINE ENGINE OIL SJ/CF 4

SAE 20W50

APPLICATION

It is a range of engine oils blended from virgin base oils, which have been fortified with performance additive. Recommended for naturally-aspirated and mildly turbo charged diesel and petrol engines.

PERFORMANCE LEVEL (API SJ/CF 4)

MEETS OR EXCEEDS:

- | | | |
|---------------------------------------|---|-----------------------------|
| • MB 227.0 MB 227.1 | * | MAC T9, MAC T8A, CAT1-A |
| • US MIL-L-46152E AND MIL-L-2104B | * | MAC EOM PLUS |
| • ADE Pg 3 | * | API SJ/CF 4 |
| • ACEA E3-96 ISUZU, ES-99,B3-98,A3-98 | * | VOLVO VDS-2 |
| • MAN 3275 | * | CUMMINS 20072, 20076, 20077 |

- Specially designed combination of detergent and dispersant additives maintains power output by controlling piston and ring deposits.
- Heavy duty engine protection in new and older engines
- High temperature deposit control in turbo charged and naturally aspirated engines
- Robust against a wide range of diesel quality
- Premium 500+ and sludge handling and oxidation stability
- Strong diesel detergency for high level piston cleanliness and extended drain capability.
- Superior wear and bearing corrosion control giving maximum engine protection.

| TYPICAL PHYSICAL CHARACTERISTICS | SAE 20W50 |
|---|------------------|
| Density @ 20°C KG/L | 0.894 |
| Viscosity Cst @ 40°C | 147 |
| Viscosity Cst @ 100°C | 17.8 |
| Viscosity Index | 132 |
| Pour Point, °C (MAX) | -18 |
| Flash Point, °C (MIN) | 250 |
| TBN mg KOH / G | 11 |