



PO BOX 9699
Bloemfontein
9300
Fax: 051 433 4337
Mobile: 082 800 4599
E-mail: bertus@fleetline.co.za
Website: www.fleetline.co.za

FLEETLINE SUPER TRACTOR OIL (STOU)

High performance, multipurpose lubricant.

APPLICATION

- Engine, Transmission, PTO, Wet Brakes etc.

PERFORMANCE LEVEL (API CF/GL-4) **MEETS OR EXCEEDS:**

- GL4 LOW SPEED / HIGH TORQUE
- CCMC D4
- JOHN DEERE J27
- REDUCED WET BRAKE NOISE
- MASSEY
- M1193
- FORD M2C-159B
- FORD 134-D

BENEFITS

Unique multi application additive package enables use in engines, transmissions, final drives and hydraulic system, avoiding costly equipment failure due to misapplication
Special friction modifier component allows smooth action of wet brakes and power take-off clutches, minimizing chatter, stick slip and squawk

TYPICAL PHYSICAL CHARACTERISTICS	SAE 20w40
Density @ 20 °C KGL	0.892
Viscosity Cst , 40 °C	134
Viscosity Cst @ 100 °C	15
Viscosity Index	114
Pour point °C (MAX)	-24
Flash point °C (MIN)	240
TBN mg KOH/ g	10.7
ZINC, m%	0.14