



PO BOX 9699  
Bloemfontein  
9300  
Fax: 051 433 4337  
Mobile: 082 800 4599  
E-mail: [bertus@fleetline.co.za](mailto:bertus@fleetline.co.za)  
Website: [www.fleetline.co.za](http://www.fleetline.co.za)

## **TWO STROKE**

Pro Viscous two stroke motor oil is a high performance mineral based two stroke engine oil formulated with specially imported low ash additives. Designed and formulated to meet the requirements of API TC performance lubricants.

### **APPLICATIONS**

Air cooled two stroke motorcycle engines  
Air cooled two stroke portable power equipment engines  
Air cooled two stroke chainsaw/brush cutter engines  
Oil injected engines (except marine outboards)

### **PERFORMANCE STANDARDS**

- API TC
- ISO-L-EGD + Level (150 index in the Honda Dio 3 hour test)
- OEM Levels (STIHL, HUSQVARNA < PAIGGIO.)
- ISO-L-EGE Level (PIAGGIO Hexagon Detergency test and SSTIHL Chain Saw test included).

### **BENEFITS**

The specially formulated blend of mineral oil and imported low ash additive provides excellent exhaust port and piston cleanliness by controlling carbon deposits therefore controlling combustion efficiency and reduced exhaust smoke. The excellent lubricity of the additive coats the contacting surfaces with an anti-wear film to protect against wear under severe conditions.

### **FINISHED OIL CHARACTERISTICS**

|                    | <b>RESULT</b> | <b>LIMIT</b> |
|--------------------|---------------|--------------|
| Colour             | Brown         |              |
| Viscosity @ 40 C   | 72.15         |              |
| @ 100 C            | 9.57          | 6.5min       |
| Flash Point PMCC C | 178           | 70 min       |
| Sulphated Ash wt%  | 0.04          | 0.18 max     |